

DESCRIPTIONS

H1Z2Z2-K/62930 IEC 131 6.0mm² Tinned Copper Non-Halogen EN 1500V

STANDARDS

IEC 60228, IEC 60332 -1-2, IEC 60754, IEC 60811 -2-1, IEC 61034, IEC 61215
 EN 50618 File No.:R50302047
 IEC 62930 File No.:R50413678
 ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded tinned copper
Size	6mm ²
Stranding	78/0.295±0.01mm
Diameter	3.0mm
Primary Insulation	XLPE
Minimum Average Thickness	0.7mm
Color	White
Secondary Insulation	XLPE
Minimum Average Thickness	0.8mm
Color	Black
Outer Diameter	6.1±0.15mm

ELECTRICAL CHARACTERISTICS

Voltage Rating	AC: 1000V; DC: Max.1500V
EN 50618/IEC 62930	
Ambient Temperature	-40°C up to 90°C
Insulation Resistance At 20°C	≥ 610 MΩ.km
Current carrying capacity AT 30°C	72A
Spark test	10000 VAC
Voltage Withstand	6500 VAC
Conductor Resistance AT 20°C	≤3.39 Ω/km

OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 5 X O.D.
Static	≥ 4 X O.D.
Ozone resistant	IEC 60811-403
Low smoke emission	IEC 61034-2,light transmittance ≥ 60%
Weathering/UL resistance	IEC 62930 Annex E
Halogen free	IEC 62821-1 Annex B
Flame retardant	IEC 60332-1-2

PRINT LEGEND

KIBOR CABLE ▲ TÜV H1Z2Z2-K 62930 IEC 131 1x6.0mm² DC 1500V HALOGEN FREE LOW SMOKE CE www.kiborcable.com

PACKAGING

- a) 250m/Roll
- b) Consulting if delivering in other ways.

Signature:
Date: